



# Delo<sup>®</sup> FleetPRO

## Heavy-Duty Diesel Engine Oil

Product Data Sheet

### Customer benefits

- Wide temperature operation: SAE 15W-40 multigrade provides good low temperature startability and high temperature protection, allowing use over a wide temperature range. SAE 20W-50 option maintains thicker oil film when operating under higher ambient temperatures, providing protection for metal parts.
- Maintain oil drain: formulated with proven metallic detergent additive system to neutralize harmful acids, helping to prevent corrosion and maintain oil drain interval.
- Maintain engine life and performance: formulated with advanced additives technology and premium base oils to provide good wear protection, deposit control and soot dispersancy performance, helping to protect the engine and running smoothly.

### Applications

The following applications whenever the manufacturer recommends SAE 15W-40 or 20W-50 multigrade lubricants meeting API CH-4 performance or below:

- Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated)
- Commercial road transport
- Off-highway vehicles
- Agricultural tractors and farm machinery
- High speed diesel engines in marine service (e.g., fishing boat, river transport)

### Performance standards

- API CH-4

### Product features:

Heavy-duty diesel engine oil specifically formulated to meet API CH-4. Robust performance designed for use in diesel engines in commercial fleets and off-highway vehicles.

A Chevron company product

All trademarks are property owned by Chevron Intellectual Property LLC.





## Typical key properties

DELO FLEETPRO	RESULTS	
SAE Grade	15W-40	20W-50
Product Code	500435	500368
Kinematic Viscosity, ASTM D445		
@ 40°C, mm <sup>2</sup> /s	109	161
@ 100°C, mm <sup>2</sup> /s	14.4	18.5
Viscosity Index, ASTM D2270	134	129
Base No., ASTM D2896, mg KOH/g	8	8
Zinc, %m	0.13	0.13
Phosphorus, %m	0.12	0.12

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

**Environment, Health and Safety** Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit [www.caltexoils.com](http://www.caltexoils.com).

For more information, go to [www.chevronlubricants.com](http://www.chevronlubricants.com)