



## SCOPE PEGASO – SM/CF

SCOPE PEGASO SM/CF is a unique fully synthetic lubricant for ultimate engine protection and performance. It is multi grade motor oil specially formulated with selected synthetic base fluids and race proven additive technology for use in passenger cars and light truck gasoline engines and diesel engines under all operating conditions.

### ➤ Main benefits

- Ultimate protection in all driving conditions.
- Low viscosity, rapid oil flow and low friction effectively contributes towards reducing fuel consumption.
- Meets environmental requirements.

### ➤ Application

SCOPE PEGASO – SM/CF fully synthetic oil can be used for all naturally aspirated, fuel injected, turbo charged and multivalve passenger car engines.

### ➤ Specifications

SCOPE PEGASO fully synthetic oil exceeds the requirements of all major car manufacturers and the following standards. API SM/CF, VW – 500.00, 502.00, 505.00, BMW - long life 98, Mercedes Benz – sheet 229.3, Porsche “GL”

### Typical Physical Characteristics

SAE Viscosity Grade	5W/40	5W/30	15W/40	5W/50	10W/30	10W/40
Vis @ 100 <sup>o</sup> c	14.50	11.50	14.50	17.00	11.0	14.50
Viscosity Index	178	165	160	195	155	168
Pour Point <sup>o</sup> c	-45	-45	-39	-42	-39	-39
Flash Point COC <sup>o</sup> c	220	220	230	220	222	222
TBN mg KOH/g	10	10	10	10	10	10
Apparent Viscosity – Cp	4500	4300	4000	4700	4000	4200
	-30 <sup>o</sup> c	-30 <sup>o</sup> c	-20 <sup>o</sup> c	-30 <sup>o</sup> c	-25 <sup>o</sup> c	-25 <sup>o</sup> c

## SCOPE PEGASO – SL/CF

SCOPE PEGASO SL/CF is a unique fully synthetic lubricant for ultimate engine protection and performance. It is multi grade motor oil formulated from selected synthetic base fluids and race proven additive technology for use in passenger cars and light truck gasoline engines and diesel engines under all operating conditions.

### ➤ Main benefits

- Ultimate protection in all driving conditions.
- Low viscosity, rapid oil flow and low friction effectively contributes towards reducing fuel consumption.
- Meets environmental requirements.

### ➤ Application

SCOPE PEGASO – SL/CF fully synthetic oil can be used for all naturally aspirated, fuel injected, turbo charged and multivalve passenger car engines.

### ➤ Specifications

SCOPE PEGASO fully synthetic oil exceeds the requirements of all major car manufacturers and the following standards. API SL/CF, VW – 500.00, 502.00, 505.00, BMW - long life 98, Mercedes Benz – sheet 229.3, Porsche “GL”. ACEA A3/B3.

### Typical Physical Characteristics

SAE Viscosity Grade	5W/40	5W/50	10W/30	10W/40	15W/40	5W/30
Vis @ 100 <sup>o</sup> c	14.50	17.00	11.0	14.50	14.50	11.00
Viscosity Index	180	195	155	168	160	165
Pour Point <sup>o</sup> c	-45	-42	-39	-39	-39	-45
Flash Point COC <sup>o</sup> c	220	218	222	222	230	220
TBN mg KOH/g	10	10	10	10	10	10
Apparent Viscosity – Cp	4500	4700	4000	4200	4000	4200
	-30 <sup>o</sup> c	-30 <sup>o</sup> c	-25 <sup>o</sup> c	-25 <sup>o</sup> c	-20 <sup>o</sup> c	-30 <sup>o</sup> c