



# Graäffett C EP 2 & 3

## Product Description

Graäffett Calcium Grease is formulated from mineral oil and calcium soap thickener and performance additives.

## Performance benefits:

- Good pumpability at low temperatures,
- Excellent water resistance,
- Good protection against corrosion and wear.
- Excellent EP properties

## Features:

- Reduced maintenance costs,
- Available in yellow, blue and red color.
- Available in different NLGI grades.

## Applications:

Graäffett Calcium Grease is suitable for use in ball and roller bearing, operating in not so demanding, low speed and lightly loaded applications at temperature from -20<sup>0</sup>C to 60<sup>0</sup>C.

Typical characteristics	Unit	Test Method	Typical Results*	
Appearance Color	Visual		Buttery and smooth yellow	
NLGI Grade		ASTM D217	2	3
Worked Penetration @25°C	10 <sup>-1</sup> mm	ASTM D217	265-295	220-250
Dropping point, min	°C	ASTM D566	80	80
Pressure oil separation 0.25PSI	%	ASTM D1742	4	4
Oxidation Stability @100°C	PSI	ASTM D942	7	7
Four Ball Weld load, min	kg	ASTM D2596	200	200
Operating temperature range	°C		-20 to +60	

Note: the information contained herein is subject to change without notification. Typical properties may vary slightly.