



SCOPE EFFOL MP – GL4

AUTOMOTIVE GEAR LUBRICANTS

SCOPE EFFOL GEAR LUBES are premium quality long life gear box oils blended with extreme pressure additives and these oils are environmentally friendly contains neither lead nor chlorine. They have oxidation resistant, thermal degradation and resist staining, rusting and corrosion and excellent resistant to foaming.

➤ **Main benefits**

- Outstanding protection against wear and rust.
- Longer drain interval and gear life.
- Good load carrying capability.
- Resistance to oxidation and oil thickening and are compatible to oil seals.
- Good low temperature performance.

➤ **Application**

SCOPE EFFOL MP GEAR LUBRICANTS are recommended for commercial vehicle's automotive and passenger car gear type transmission and drive axles operating up to 100°C, Hypoid gear, and contractor equipment and in worm gear final drives.

➤ **Specification**

SCOPE EFFOL MP Gear lubes meets the performance requirements of API service GL-4 and U.S Military Specification MIL-L-21055C

Typical Physical Characteristics

SAE Viscosity Grades	90	140	80W90	85W90	85W140
Viscosity, cSt @ 100° c	18.50	30.20	14.60	18.00	29.00
Viscosity Index	96	95	101	100	98
Pour Point	-12	-9	-24	-18	-9
Flash Point COC	248	260	240	244	250