

VOYAGER SJ 20W/50, 40

DESCRIPTION

Voyager SJ is a high quality Gasoline engine oils for use in passenger cars and light trucks. It is formulated from selected base oils and special chemical additives which provide oxidation stability and high detergent and dispersant characteristics.

APPLICATIONS

Voyager SJ is recommended for supercharged or naturally aspirated Gasoline engines, in passenger cars and light trucks requiring the manufacturer's recommended API service category SJ. It can also be used where lower API level oils are recommended.

BENEFITS:

- High oxidation stability.
- Protects against wear, rust, corrosion and sludge formation.
- Minimize deposit formation at high temperatures.

PERFORMANCE LEVEL

APISJ/CF

PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE		TEST METHOD
Grade		-	20W/50	40	-
Specific Gravity	@ 15°C	-	0.8900	0.8850	ASTM D-1298
Viscosity	@ 40°C	mm ² /s	162.3	135.0	ASTM D-445
	@ 100°C	mm ² /s	17.75	13.75	ASTM D-445
Viscosity Index		-	120	97	ASTM D-2270
Flash Point	COC	°C	240	250	ASTM D-92
Pour Point		°C	-27	-15	ASTM D-97
Base Number		mg KOH/g	6	6	ASTM D-2896
Color		-	Red	L3.0	VISUAL/ASTM D-1500
CCS Vis	@ -15°C	cP	8500	-	ASTM D-5293