

MSDS

(Material Safety Data Sheet)

SECTION #1 PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: TOTAL CARTER EP 68, 100, 150, 220, 320 460, 680 and 1000

CHEMICAL NAME AND SYNONYMS: MIXTURE

MANUFACTURER/SUPPLIER'S NAME:

TOTAL LUBRICANTS CANADA INC. 220, LAFLEUR LASALLE, QUEBEC H8R 4C9 Tel.: (514) 595-7579 or 1-800-463-3955

24 HOURS EMERGENCY: Call CHEMTREC 1-800-424-9300 or 703-527-3887

PRODUCT USE: EP LUBRICANT FOR INDUSTRIAL GEARS

WHMIS CLASS AND DESCRIPTION -

These products are not regulated by the WHMIS.

SECTION #2 COMPOSITION/INFORMATION ON INGREDIENTS

NOM	%	No CAS

ADDITIONAL REGULATORY INFORMATION

- No hazardous ingredients as defined by the Canadian Hazardous Products Act (BILL C70) or by OSHA 29 CFR 1910.1200.
- Canadian DSL status: All ingredients are listed.
- * No components of this product have been found carcinogenic or potential carcinogen. Does not contain ingredients that are listed as carcinogenic or potential carcinogen by OSHA, IARC or the U.S. National Toxicology Program (NTP). This product or its components have no teratogenic or mutagenic effects known.

888.654.4095

Fax: 418.522.6717

SECTION #3 PHYSICAL DATA

PHYSICAL STATE AT 25°C **BOILING POINT:** POUR POINT: DENSITY (g/cm³ at 15°C): VAPOR PRESSURE (mm Hg at 20°C): VISCOSITY (cSt at 100°C): pH: **EVAPORATION RATE:** SOLUBILITY IN WATER: APPEARANCE ET ODOR:

Liquid > 250°C < 0°C 0,87 to 0,91 Negligible 8 to 100 No Object Negligible Negligible Yellowish to amber liquid with characteristic odor

STABILITY AND REACTIVITY **SECTION #4**

STABILITY: **CONDITIONS TO AVOID:**

PRODUCTS TO AVOID: HAZARDOUS DECOMPOSITION PRODUCTS: **POLYMERIZATION:**

Stable Avoid excessive heat, open flames and formation of oil mist. Oxidizing agents, strong acids and bases. N/A Will not occur

SECTION #5 FIRE FIGHTING MEASURES

FLASH POINT (COC):	> 220°C
FLAMMABILITY LIMITS IN AIR:	LEL: N/A
(% PER VOLUME)	UEL: N/A
AUTOIGNITION TEMPERATURE (°C):	N/A
EXTINGUISHING MEDIA:	Foam, Dry chemical and CO ₂
HAZARDOUS COMBUSTION PRODUCTS:	Normal combustion products, CO and CO ₂ .
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without adequate protective clothing and an approved positive self-contained breathing apparatus. Use water to cool fire exposed containers.

TOTAL LUBRIFIANTS CANADA INC. 514.595.7579 800.463.3955 Tél.:

220, Ave Lafleur Fax: 514.367.5767

LaSalle Qc H8R 4C9

QUÉBEC; Tél.: 418.522.4095 PICKERING (ON): Tel.: 905.831.9569

888.654.4095 Fax: 418.522.6717

SECTION #6 TOXICOLOGICAL INFORMATION

	SPECIES	LD ₅₀ ORAL	LD ₅₀ DERMAL	LC50 INHALATION	HRS
	Rat	> 5000 mg/Kg	> 2000 mg/Kg	N/A	
INH	IHALATION: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation the respiratory passages. Exposure limit to the mist = 5 mg/m ³ (TLV/TWA, ACGIH).				
CON	CONTACT WITH EYES : This product should not cause eye irritation. Repeated and prolonged contact				rolonged contact may
.	cause eye irritation.				
SKI	N CONTACT:		s product should not cause skin irritation. Prolonged and repeated contact with		
ING	ESTION:		this product can cause skin drying, which may result in skin irritation and dermatitis. May cause nausea.		
SEC	CTION #7	ACCIDENTAL RE	LEASE MEASURES	6	
SPILL AND LEAK PROCEDURES:		re	Eliminate all ignition sources. Stop leak only if safe to do so. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal.		
SEC	CTION #8	HANDLING AND STORAGE			
STORAGE AND HANDLING:			Store in cool, dry, ventilated area, away from heat and ignition sources. Use good personal hygiene. Always keep the container close.		
SEC		EXPOSURE CONTROLS / PERSONAL PROTECTION			
	CTION #9	EXPOSURE CON	ITROLS / PERSONA	AL PROTECTION	
	CTION #9		ITROLS / PERSONA Mechanical ventilation is		
VEN		Ν	lechanical ventilation is		ommended.
VEN		M CTION: If	Aechanical ventilation is finist present, chemical of	recommended.	
VEN RES GLC	ITILATION: SPIRATORY PROTE	CTION: If R h	Mechanical ventilation is mist present, chemical e Resistant gloves (Viton,	recommended. cartridge respirator is reco Nitrile, Neoprene) are	

220, Ave Lafleur LaSalle Qc H8R 4C9 Fax: 514.367.5767

QUÉBEC; Tél.: 418.522.4095 888.654.4095 Fax: 418.522.6717 PICKERING (ON): Tel.: 905.831.9569

SECTION #10 DISPOSAL CONSIDERATIONS

FIRST AID

WASTE DISPOSAL METHODS:

SECTION #11

Consult relevant local authorities. Reclaim or dispose of at a licensed waste disposal company. Incinerate with approval of appropriate local authority.

INHALATION:	Remove person to fresh air. See a physician if irritation persists.			
CONTACT WITH EYES:	Flush immediately with water for at least 15 minutes.			
CONTACT WITH SKIN:	Wash contaminated skin with mild soap and water. See a physician if irritation persists.			
INGESTION:	This product has a low toxicity. May cause nausea and have a laxative effect. Do not induce vomiting. Contact an Anti-Poison Center (1-800-463-5060).			

SECTION #12 HAZARDS IDENTIFICATION

INHALATION: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation to the respiratory passages. Exposure limit to the mist = 5 mg/m³ (TLV/TWA, ACGIH).

- **CONTACT WITH EYES**: This product should not cause eye irritation. Repeated and prolonged contact may cause eye irritation.
- **SKIN CONTACT**: This product should not cause skin irritation. Prolonged and repeated contact with this product can cause skin drying, which may result in skin irritation and dermatitis.
- **INGESTION**: May cause nausea.

SECTION #13 ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.

BIODEGRADABILITY: NOT READILY BIODEGRADABLE.

 TOTAL LUBRIFIANTS CANADA INC.

 Tél.:
 514.595.7579
 800.463.3955

220, Ave Lafleur Fax: 514.367.5767

LaSalle Qc H8R 4C9

QUÉBEC; Tél.: 418.522.4095 888.654.4095 PICKERING (ON): Tel.: 905.831.9569

Fax: 905.831.6240

Fax: 418.522.6717

SECTION #14 TRANSPORTATION INFORMATION

TRANSPORTATION (TDG)

SHIPPING NAME:	None
UN NUMBER:	None
CLASS DESCRIPTION:	None

REGULATORY INFORMATION SECTION #15

This product has been classified in accordance with the hazard criteria of the Controlled Products. Regulations (CPR) and the MSDS contains all the information required by the CPR.

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.

Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

SECTION #16 ADDITIONAL INFORMATION

Prepared by: Francis Bossé, Chemist

Revised on: 21 JUNE 2011

We believe that technical information and recommendations contained herein to be reliable and accurate. However, we provide these data without warranty or guarantee of any kind, expressed or implied. We assume no responsibility for any loss, damage, or expense, direct or consequential, arising from the use of products described herein.

TOTAL LUBRIFIANTS CANADA INC. 514.595.7579 800.463.3955 Tél.:

220, Ave Lafleur Fax: 514.367.5767

LaSalle Qc H8R 4C9

Tél.: 418.522.4095 QUÉBEC: PICKERING (ON): Tel.: 905.831.9569

888,654,4095 Fax: 418.522.6717