



Graäfett Transparent

Product Description

Graäfett Transparent Grease formulated from superior blended base oils, proprietary thickener and selected high performance additives for improving properties.

Performance benefits:

- Excellent anti-wear properties,
- Excellent water washout resistance and rust inhibition
- Good oxidation stability,
- Excellent mechanical stability

Features:

- Broad compatibility,
- Reduced maintenance costs,
- Available in yellow, blue and red color.
- Available in different NLGI grades.

Applications:

Graäfett Transparent Grease is suitable for use in wheel bearings, ball joints, joints in the cars, fans, conveying systems at temperature from -20°C to 120°C.

Typical characteristics	Unit	Test Method	Typical Results *	
Appearance	Visual		Buttery and smooth	
Color			transparent	
NLGI Grade		ASTM D217	2	3
Worked Penetration @25°C	10 ⁻¹ mm	ASTM D217	265 – 295	220 – 250
Dropping point, min	°C	ASTM D566	180	180
Pressure Oil Separation, 24hrs, max	%	ASTM D1742	5	3
Oxidation Stability @100°C, 96hrs, max	PSI	ASTM D942	5	5
Water Washout @ 80°C, max	%	ASTM D1264	15	15
Base Oil Viscosity @40°C	cSt	ASTM D446	100	100
Operating temperature range	°C		-20 to +120	

Note: the information contained herein is subject to change without notification. Typical properties may vary slightly.