



SCOPE PERFO 8000 – API SL/CF

SCOPE PERFO 8000 are designed to prepare for all gasoline and diesel powered passenger cars, light trucks and van including those fitted with turbo chargers. Originated with highly refined base stock and efficient additive technology to maintain engine oil cleanliness, wear and very good low temperature fluidity ensure easy starting in cold weather and low volatility contributes to low oil consumption.

➤ Main benefits

- Fuel economy and better cold starting.
- Excellent engine protection in severe weather conditions.
- Thermal stable. Anti-wear, anti-oxidant and long drain interval.
- Low oil consumption and turbo proven stability.
- Oxidation resistant, good high temperature stability.
- Longer drain interval.
- Low oil consumption

➤ Application

SCOPE PERFO 8000 oil is recommended in severe operating condition where high performance oils are required.

➤ Specification

SCOPE PERFO 8000 meets and exceeds the requirements of API SL/CF and can be used in all types of cars and light duty trucks. The product also meets ACEA E2-96 issue 3, ACEA A3-98/B3-98 issue 2/B4-02, MB 229.1, MAN 270/271, VOLVO VDS, MACK EO-L, MTU/DDU TYPE-1, ALLISION – C4

Typical Characteristics

SAE Viscosity Grade	10W/40	15W/40	20W/50	20W/40	40	50
Viscosity, cSt @ 100° c	14.50	15.00	18.50	15	15	19
Viscosity Index	147	138	126	114	97	97
Pour Point, °c	-33	-30	-24	-24	-15	-12
Flash Point CoC °c	216	220	230	230	248	258
TBN ASTM D 2896	10	10	10	10	10	10
Apparent Viscosity – Cp	6500 -25° c	6300 -25° c	7800 -15° c	7700 -15° c	-	-